

भारत सरकार / Government of India भारतीय पुरातत्व सर्वेक्षण / Archaeological Survey of India जोधपुर मंडल, जोधपुर / Jodhpur Circle

fufonk I wuk

अधीक्षण पुरातत्वविद्, भारतीय पुरातत्व सर्वेक्षण, जोधपुर मंडल, जोधपुर, भारत के राष्ट्रपति की ओर से निम्नलिखित कार्य हेतु प्रमाणित एवं उपर्युक्त श्रेणी में पंजीकृत एवं पात्र ठेकेदारो/पंजीकृत फर्म से केवल मुहर बंद मदवार/प्रतिशत दर आधार पर सम्पूर्ण मद कार्य के लिए जो भी लागू हो निविदायें आमंत्रित करते है। निम्न वर्णित कार्य की निविदा **dk; ky; lgk; d v/kh{k.k igkrRofon} dkyhcæk lægky;] dkyhcæk] ft yk gu@kux<+**में दिनांक 02.03.2016 को 3.00 बजे तक प्राप्त की जावेगी, तथा उसी दिन अपराहं 3.30 बजे खोली जावेगी।

निविदा क्र.सं	कार्य का नाम	अनुमानित लागत रू.	धरोहर राशि रू.
03	dkyhcaxk laxÿky; e≇CCTV dsej≇llykbZgsrn≬	4,80,265/-	10,000 /

जिन अधिकृत डीलर/निर्माताओं की मुहर बंद निविदा आवेदन के साथ धरोहर राशि अधीक्षण पुरातत्वविद्, भारतीय पुरातत्व सर्वेक्षण, जोधपुर के पक्ष में जारी बैंक मांग पत्र/एफडीआर के रूप में संलग्न नही होगी एंव मुहर बंद निविदा लिफाफे पर कार्य का नाम व निविदा कर्ता का नाम अंकित नही होगा वह अमान्य होगी।

\hat{U} furfork i i = ds fy, $kr \hat{U}$

1. टेण्डरकर्ता संबंधीत क्षेत्र में अधिकृत डीलर / के.लो.नि.वि. / स्थानीय लो.नि.वि. विद्युत विभाग में रजिस्टर्ड फर्म होने चाहिए और वैध TAN एवं PAN होने अनिवार्य।

- 2. निविदा एवं आवश्यक सूचना भा.पु.स. की वेबसाईट www.asi.nic.in/www.asijodhpurcircle.in पर उपलब्ध है। निविदा प्रपत्र के साथ शुल्क रू. 500 / का मांग पत्र अधीक्षण पूरातत्वविद, जोधपूर मंडल के नाम जयपूर में देय अपने आवेदन के साथ संलग्न कर प्राप्त कर सकते है।
- 3. यदि निविदा प्रपत्र बिकीं / प्राप्ति दिवस को अवकाश घोषित होता है, तो ऐसी स्थिति में निविदा प्रपत्र बिकी / प्राप्ति अगला कार्य दिवस होगा।

4-d`i;k V\$Mj QkeZHkjusIsinoZlayXu fu;e ,oe~'kr3/;ku ino2d i<\$1

अधीक्षण पुरातत्वविद् (प्रभारी)

PRICE OF TENDER: Rs. 500/-

भारत सरकार / Government of India भारतीय पुरातत्व सर्वेक्षण / Archaeological Survey of India जोधपुर मंडल, जोधपुर / Jodhpur Circle, Jodhpur

ITEMWISE LIMITED TENDER FOR EXECUTION OF WORK

Date of Opening: 02-03-2016 at Kalibangan Museum, Kalibangan, Dist. Hanumangarh.

Name of Work: Supply of CCTV Cameras in Kalibangan Museum, District Hanumangarh, Rajasthan.

I/We hereby tender for execution of work for the President of India described in the under mentioned memorandum according to the specification within the time specified and at the rates specified therein subject to the conditions of the contract.

MEMORANDUM

(i) Earnest Money: **Rs. 10,000/-**

- (ii) Security Deposit: As per the terms and condition (10% in FDR)
- (iii) PAYABLE IMMEDIATELY ON THE ACCEPTANCE OF TENDER: EMD will be adjusted against the total Security Deposit
- (iv) PERCENTAGE TO BE DEDUCTED FROM RUNNING BILL: Remaining amount will be deducted as per the rates given in the terms and conditions
- (v) ESTIMATED COST: Rs. 4,80,265/-
- (vi) PLACE OF SUPPLY: Kalibangan Museum, Kalibangan, Dist Hanumangarh

READ TERMS AND CONDITIONS BEFORE FILLING UP THE SCHEDULE. SIGN ON ALL PAGES

SI.No.	Description or specification of the items of material to be supplied	Total Estimated Quantities	Time allowed for supply	Delivery	Rate in figures and words (excl. VAT/Service Tax)	Unit	Amount in figures and words
	Part – I CCTV Cameras and Network						
A	Provision for supply of CCTV camera, NVR, LED, hard disk etc of reputed brand.						
1.	3 MP IP Network IR bullet camera having the basic configurations as per Annexure-I.		15 Days	Kalibangan Museum, Kalibangan, Dist. Hanumangarh	Rs.	Nos.	Rs.

CPWD-9 Tender

Tender No: 4 /2015-16 F.No. 06/04/JDH/KLB Reorg/2015-16- Tech



2.	16 channel NVR with 2 port of compatible make	1 Nos.			Rs.	— Nos.	Rs.
3.	4 TB hard disk of reputed make	2 Nos.			Rs.	— Nos.	Rs.
4.	42" LED Display monitor of reputed make	1 Nos.			Rs.	— Nos.	Rs.
В	Provision for supply	of accessori	es, cables wit	th ISI speci	fications and installa	ation, net	working and
	commissioning of CC	CTV Cameras	S.				
1.	Power Supply unit 16 channel	1 Nos.			Rs.	— Nos.	Rs.
2.	Cat 6 Cable for net working	800 Mtr.			Rs.	— Mtr.	Rs.
3.	PVC Conduit pipe	60 Nos.			Rs.	Nos.	Rs.
4.	Installation and testing	Job			Rs.	Job	Rs.
						100	

Note: The total tender should be for complete supply of materials and not for one or few items. The rate should include all taxes and other charges as applicable. If quoted for part of the materials, the tender will be rejected.

Signature and seal of the Firm/Authorised signatory

Should this tender be accepted, I/We hereby agree to abide by and fulfil all the terms and provisions of the said conditions annexed hereto so far as applicable, and/or in default thereof to forfeit and pay to the President of India or his successor in office the sum of money mentioned in the said conditions. A sum of Rs.______* is herewith forwarded in Cash/Treasury Challan/DD/FDR as earnest money. If I/We fail to commence the work to specified in the above memorandum or if I/We fail to deposit the amount of security deposit specified against (ii) in the above memorandum in accordance with clause 1 of the said conditions of firm I/We agree that the said President or his successors in office shall, without prejudice to any other right or remedy, shall be retained by his towards such security deposit. I/We further agree that the said President or his successors in office shall also be at liberty to cancel the acceptance of the tender if I/We fail to deposit security amount to aforesaid.

* Give particulars & numbers

Signature and seal of firm

Address

Signature of witness to Signature of tender

Address

Dated the 2016

The above tender is hereby accepted by me behalf of the President of India.

Dated :

Signature of the officer by whom the tender is accepted

Superintending Archaeologist

Terms & Condition of Tender

1. Tenders should always be placed in sealed covers (waxsealed/tape sealed/gum sealed) with the name of the work written on the envelopes.

2. Earnest money should be submitted in the form of Demand Draft drawn in favour of the Superintending Archaeologist, Jodhpur Circle on a Scheduled Bank /FDR duly pledged in favour of the Superintending Archaeologist, Jodhpur Circle must accompany each tender.

3. The firm, whose tender is accepted, will be required to furnish (unless exempted) a security deposit for the due fulfilment of his contract, such sum as will amount.

• 10% in the case of works costing up to Rs. 1, 00,000/- and above of the estimated cost of the work put to tender.

4. The Security Deposit will be collected by the deductions from the running bill of the firm at the rates mentioned above. The Earnest Money Deposit placed at the time of tender will be treated as a part of the security deposit. The security amount will also be accepted in shape of Demand Draft in favour of Superintending Archaeologist, Jodhpur Circle/ FDR pledged in favour of Superintending Archaeologist, Jodhpur Circle etc. drawn on Scheduled Banks.

5. Special care should be taken to write the rates and amounts in figures as well as in words and in such a way that interpretation is not possible. In case of figures the words 'Rs'. should be written before the figures of rupees and word 'p' after the decimal figures and in case of words the words Rs Proceeds and the word paisa should be written at the end. Unless the rate is in whole rupees and not followed by the word 'ONLY', it's should invariably be up to two decimal places. While quoting the rates in the schedule of quantities the rate in words should be written closely following the figure and it would not be written in the next line.

6. The firm should quote the rate and amount in figure as well as in words. The amount for each item should be worked out and the total for all items should be given.

7. Rates quoted by the firm in item rate tender in figures and words shall be accurately filled in so that there is no discrepancy in the rates written in figures and words.

8. Whenever the rates quoted by the firm in figures and in words tally but the amount is not worked out correctly, the rate quoted by the firm will be taken as correct and not the amount.

9. The rate quoted should include all VAT/Sales tax etc. ASI will not entertain any claim whatsoever in this regard.

- 10. In case firm's signature on tender is fixed in an Indian Language, the rate/ amount/ percentage above or below should also be written in the same language. In the case of illiterate firms the rates/percentage should be attested by a witness.
- 11. The tender should be signed by the firm/authorised signatory in case of a firm. All tenders should have the signature of a witness. The seal of the firm/firm should be fixed below the signature.
- 12. All corrections/over writings in case of rate/amount/ percentage etc. should be duly attested with signature of the firm/ authorised signatory.
- 13. The discretion of acceptance of a tender, will rest with the Circle/Branch Officer/Regional Director/ Director General, A.S.I who does not bind himself to accept the lowest tender, and reserve to himself the authority to reject any or all of the tenders received, without the assigning any reason. Any tender, in which any of the prescribed conditions are not fulfilled or are incomplete in any respect is liable to be rejected.
- 14. Canvassing in connection with tenders is strictly prohibited and the tender submitted by the firms who resort to canvassing is liable to rejected.

- 15. On the issue of the work order, the firm will execute the work. If he fails to do so within the stipulated time or he withdraws afterwards, his EMD will be forfeited in full. No enhancement of rates for any reason will be permitted after opening of the tender.
- 16. On acceptance of the tender, the name of the accredited representative(s) of the firm who would be responsible for taking instructions for the Circle/Branch Officer shall be communicated to the Circle/Branch Officer.
- 17. The firm must produce income-tax clearance certificate in revised form as notified under Ministry of Finance O.M No. 67/30/69/ITAE dated 2nd July, 1970, and other relevant documents before the tender can be sold to him. If he downloads the same from website, he should enclose them with the tender. If he found to be ineligible, his tender will be rejected.
- 18. The firm shall not be permitted to tender for works in the Archaeological Survey of India, Circle/Branch Office (Responsible for award and execution of contracts) in which his near relative is posted as an officer in any capacity.
- 19. No engineer of Gazetted rank or other Gazetted Officer employed in Engineering or Administrative duties in an Engineering Department of the Government of India is allowed to work as a firm for a period of two years of his retirement from Government service, without the previous permission of the Government of India as aforesaid before submission of the tender or engagement in the firm's service.
- 20. The tender of the work shall not be witnessed by a firm or firms who himself/themselves/has /have tendered or who may tender for the some work.
- 21. The tenderer apart from being a class II (B&R) firm must associate himself with agencies of the appropriate class which are eligible to tender for sanitary and water supply and drainage installation.

- 22. The firm shall comply with the provisions of the Apprentices Act, 1961, and the rates and orders issued there under from time to time. If he fails to do so, his failure will be a breach of the contract and the Circle/Branch officer may in his discretion cancel the contract. The firm shall also be liable for any pecuniary liability arising on account of any violation by him of the provisions of the Act.
- 23. Firm should visit the working site prior to tendering.
- 24. The material should be supplied / Work executed as per the specification.
- 25. Arrangement for water/ scaffolding/ T&P articles will be made by the firm
- 26. The supply of materials is subject to voids as per CPWD/IS/ASI specifications.
- 27. The quantity of work/materials can be increased/decreased at the site during work or before placing work/supply order.

Signature of the firm Authorised signatory with seal Superintending Archaeologist

<u>Annexure-I</u>

Specifications for Cameras

Image SeriorImage SeriorMin. illumination0.095 lux@F1.4 0 lux with IRShutter time1/30s ~ 1/100,000sLens2.8 ~ 12 mm @F1.4,Angle of view:98* ~ 30.5°Compression standardVideo compressionH.264 / MJPEG Bit rate 32 Kbps ~ 16 MbpsAudio compressionC95 G.711 / G.726 Audio bit rate (-S) 64Kbps (G.711) / 16Kbps (G.726)ImageMax. image resolutionMax. image resolution2048 × 1536Frame rate60H2: 15fps (2048 x 1536), 30fps (1920 × 1080), 30fps (1280 x 720)Image settingsSaturation, brightness, contrast adjustable through client software or web browserNetworkNASAlarm triggerMotion detection, tampering alarm, network disconnect, IP address conflict, storage full, storage errorProtocolsTCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, UPNP, ICMP, IGMP,SNMP, FTP, 802.1X, QoS, HTTPSSystem compatibilityONVIF, PSIA, CGI General functionalities User authentication, watermark, dual streamInterfaceVCommunication interface 1RJ45 10M / 100M Ethernet portOn-board storageBuilt-in Micro SD/SDHC/SDXC card slot, up to 64 GBGeneral-30 °C ~ 60 °C (-22 °F ~ 140 °F), humidity 95% or less (non-condensing)Power supplyDC12V ± 10%,Power consumptionMax 5.5W (7.5W with ICR on)	Image sensor:	1/3" progressive scan CMOS				
Shutter time 1/30s ~ 1/100,000s Lens 2.8 ~ 12 mm @F1.4, Angle of view: 98 ~ 30.5° Compression standard . Video compression H.264 / MJPEG Bit rate 32 Kbps ~ 16 Mbps Audio compression (-S) G.711 / G.726 Audio bit rate (-S) 64Kbps (G.711) / 16Kbps (G.726) Image . Max. image resolution 2048 × 1536 Frame rate 60Hz: 15fps (2048 x 1536), 30fps (1920 × 1080), 30fps (1280 x 720) Image settings Saturation, brightness, contrast adjustable through client software or web recerrecerrecerrecerrecerrecerrecerre	-					
Lens2.8 ~ 12 mm @F1.4,Angle of view:98° ~ 30.5°Compression standardVideo compressionH.264 / MJPEG Bit rate 32 Kbps ~ 16 MbpsAudio compression(-S) G.711 / G.726 Audio bit rate (-S) 64Kbps (G.711) / 16Kbps (G.726)ImageMax. image resolution2048 × 1536Frame rate60Hz: 15fps (2048 x 1536), 30fps (1920 × 1080), 30fps (1280 x 720)Image settingsSaturation, brightness, contrast adjustable through client software or web browserNetworkNetwork storageNASAlarn triggerMotion detection, tampering alarm, network disconnect, IP address conflict, storage full, storage errorProtocolsTCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPOE, SMTP, NTP, UPnP, ICMP, IGMP, SNMP, FTP, 802.1X, QoS, HTTPSSystem compatibilityONVIF, PSIA, CGI General functionalities User authentication, watermark, 		-				
Angle of view: 98° ~ 30.5° Compression standard						
Or Person standard Video compression H.264 / MJPEG Bit rate 32 Kbps ~ 16 Mbps Audio compression (-5) G.711 / G.726 Audio bit rate (-S) 64Kbps (G.711) / 16Kbps (G.726) Image Emate (-S) G.711 / G.726 Audio bit rate (-S) 64Kbps (G.711) / 16Kbps (G.726) Image 2048 × 1536 Frame rate 60Hz: 15fps (2048 × 1536), 30fps (1920 × 1080), 30fps (1280 × 720) Image settings Saturation, brightness, contrast adjustable through client software or web rowser Network web rowser Network Motion detection, tampering alarm, network disconnect, IP address conflict, storage full, storage error Protocols TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, UPnP, ICMP, IGMP, SNMP, FTP, 802.1X, QoS, HTTPS System compatibility ONVIF, PSIA, CGI General functionalities User authentication, watermark, dual stream Interface Interface Communication interface 1 RJ45 10M / 100M Ethernet port On-board storage Built-in Micro SD/SDHC/SDXC card slot, up to 64 GB General -30 °C ~ 60 °C (-22 °F ~ 140 °F), humidity 95% or less (non-condensing) Power supply DC12V ± 10%,		_ ,				
Yieo compression H.264 / MJPEG Bit rate 32 Kbps ~ 16 Mbps Audio compression (-5) G.711 / G.726 Audio bit rate (-S) 64Kbps (G.711) / 16Kbps (G.726) Image 2048 × 1536 Frame rate 60Hz: 15fps (2048 x 1536), 30fps (1920 × 1080), 30fps (1280 x 720) Image settings Saturation, brightness, contrast adjustable through client software or web rowser Network Network storage NAS Alarm trigger Motion detection, tampering alarm, network disconnect, IP address conflict, storage full, storage error Protocols TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, UPnP, ICMP, IGMP, SNMP, FTP, 802.1X, QoS, HTTPS System compatibility ONVIF, PSIA, CGI General functionalities User authentication, watermark, dual stream Interface Communication interface 1 RJ45 10M / 100M Ethernet port On-board storage Built-in Micro SD/SDHC/SDXC card slot, up to 64 GB General -30 °C ~ 60 °C (-22 °F ~ 140 °F), humidity 95% or less (non-condensing) Power supply DC12V ± 10%,	-	98 30.5				
Audio compression (-S) G.711 / G.726 Audio bit rate (-S) 64Kbps (G.711) / 16Kbps (G.726) Image 2048 × 1536 Max. image resolution 2048 × 1536), 30fps (1920 × 1080), 30fps (1280 x 720) Image settings 60Hz: 15fps (2048 x 1536), 30fps (1920 × 1080), 30fps (1280 x 720) Image settings Saturation, brightness, contrast adjustable through client software or web routed between web Network NAS Alarm trigger Motion detection, tampering alarm, network disconnect, IP address conflict, storage full, storage error Protocols TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, UPnP, ICMP, IGMP, SNMP, FTP, 802.1X, QoS, HTTPS System compatibility ONVIF, PSIA, CGI General functionalities User authentication, watermark, dual stream Interface Interface Communication interface 1 RJ45 10M / 100M Ethernet port On-board storage Built-in Micro SD/SDHC/SDXC card slot, up to 64 GB General -30 °C ~ 60 °C (-22 °F ~ 140 °F), humidity 95% or less (non-condensing) Power supply DC12V ± 10%,	•					
ImageMax. image resolution2048 × 1536Frame rate60Hz: 15fps (2048 × 1536), 30fps (1920 × 1080), 30fps (1280 × 720)Image settingsSaturation, brightness, contrast adjustable through client software or web browserNetworkNetworkNetwork storageNASAlarm triggerMotion detection, tampering alarm, network disconnect, IP address conflict, storage full, storage errorProtocolsTCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, UPnP, ICMP, IGMP,SNMP, FTP, 802.1X, QoS, HTTPSSystem compatibilityONVIF, PSIA, CGI General functionalities User authentication, watermark, dual streamInterfaceInterfaceCommunication interface 1RJ45 10M / 100M Ethernet portOn-board storageBuilt-in Micro SD/SDHC/SDXC card slot, up to 64 GBGeneral-30 °C ~ 60 °C (-22 °F ~ 140 °F), humidity 95% or less (non-condensing)Power supplyDC12V ± 10%,	•					
Max. image resolution2048 × 1536Frame rate60Hz: 15fps (2048 × 1536), 30fps (1920 × 1080), 30fps (1280 × 720)Image settingsSaturation, brightness, contrast adjustable through client software or web browserNetworkNetworkMASAlarm triggerMotion detection, tampering alarm, network disconnect, IP address conflict, storage full, storage errorProtocolsTCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, UPnP, ICMP, IGMP,SNMP, FTP, 802.1X, QoS, HTTPSSystem compatibilityONVIF, PSIA, CGI General functionalities User authentication, watermark, dual streamInterfaceItal StreamCommunication interface 1RJ45 10M / 100M Ethernet portOn-board storageBuilt-in Micro SD/SDHC/SDXC card slot, up to 64 GBGeneral-30 °C ~ 60 °C (-22 °F ~ 140 °F), humidity 95% or less (non-condensing)Power supplyDC12V ± 10%,	Audio compression	(-S) G.711 / G.726 Audio bit rate (-S) 64Kbps (G.711) / 16Kbps (G.726)				
Frame rate60Hz: 15fps (2048 x 1536), 30fps (1920 x 1080), 30fps (1280 x 720)Image settingsSaturation, brightness, contrast adjustable through client software or webbrowserNetworkNASAlarm triggerMotion detection, tampering alarm, network disconnect, IP address conflict, storage full, storage errorProtocolsTCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPOE, SMTP, NTP, UPnP, ICMP, IGMP,SNMP, FTP, 802.1X, QoS, HTTPSSystem compatibilityONVIF, PSIA, CGI General functionalities User authentication, watermark, dual streamInterfaceImage soft of the soft	Image					
Image settingsSaturation, brightness, contrast adjustable through client software or web browserNetworkNASNatur triggerNASAlarm triggerMotion detection, tampering alarm, network disconnect, IP address conflict, storage full, storage errorProtocolsTCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, UPnP, ICMP, IGMP,SNMP, FTP, 802.1X, QoS, HTTPSSystem compatibilityONVIF, PSIA, CGI General functionalities User authentication, watermark, dual streamInterfaceImage Subtraction interface 1Communication interface 1RJ45 10M / 100M Ethernet portOn-board storageBuilt-in Micro SD/SDHC/SDXC card slot, up to 64 GBGeneral-30 °C ~ 60 °C (-22 °F ~ 140 °F), humidity 95% or less (non-condensing)Power supplyDC12V ± 10%,	Max. image resolution	2048 × 1536				
web browserNetworkNetwork storageNASAlarm triggerMotion detection, tampering alarm, network disconnect, IP address conflict, storage full, storage errorProtocolsTCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPOE, SMTP, NTP, UPnP, ICMP, IGMP,SNMP, FTP, 802.1X, QoS, HTTPSSystem compatibilityONVIF, PSIA, CGI General functionalities User authentication, watermark, dual streamInterfaceCommunication interface 1RJ45 10M / 100M Ethernet portOn-board storageBuilt-in Micro SD/SDHC/SDXC card slot, up to 64 GBGeneralOperating conditions-30 °C ~ 60 °C (-22 °F ~ 140 °F), humidity 95% or less (non-condensing)Power supplyDC12V ± 10%,	Frame rate	60Hz: 15fps (2048 x 1536), 30fps (1920 × 1080), 30fps (1280 x 720)				
NetworkNetwork storageNASAlarm triggerMotion detection, tampering alarm, network disconnect, IP address conflict, storage full, storage errorProtocolsTCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, UPnP, ICMP, IGMP,SNMP, FTP, 802.1X, QoS, HTTPSSystem compatibilityONVIF, PSIA, CGI General functionalities User authentication, watermark, dual streamInterfaceInterfaceCommunication interface 1RJ45 10M / 100M Ethernet portOn-board storageBuilt-in Micro SD/SDHC/SDXC card slot, up to 64 GBGeneral-30 °C ~ 60 °C (-22 °F ~ 140 °F), humidity 95% or less (non-condensing)Power supplyDC12V ± 10%,	Image settings	Saturation, brightness, contrast adjustable through client software or				
Network storageNASAlarm triggerMotion detection, tampering alarm, network disconnect, IP address conflict, storage full, storage errorProtocolsTCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, UPnP, ICMP, IGMP,SNMP, FTP, 802.1X, QoS, HTTPSSystem compatibilityONVIF, PSIA, CGI General functionalities User authentication, watermark, dual streamInterfaceImmediate 1Communication interface 1RJ45 10M / 100M Ethernet portOn-board storageBuilt-in Micro SD/SDHC/SDXC card slot, up to 64 GBGeneral-30 °C ~ 60 °C (-22 °F ~ 140 °F), humidity 95% or less (non-condensing)Power supplyDC12V ± 10%,	web browser					
Alarm triggerMotion detection, tampering alarm, network disconnect, IP address conflict, storage full, storage errorProtocolsTCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, UPnP, ICMP, IGMP,SNMP, FTP, 802.1X, QoS, HTTPSSystem compatibilityONVIF, PSIA, CGI General functionalities User authentication, watermark, dual streamInterfaceInterfaceCommunication interface 1RJ45 10M / 100M Ethernet portOn-board storageBuilt-in Micro SD/SDHC/SDXC card slot, up to 64 GBGeneral-30 °C ~ 60 °C (-22 °F ~ 140 °F), humidity 95% or less (non-condensing)Power supplyDC12V ± 10%,	Network					
Conflict, storage full, storage errorProtocolsTCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, UPnP, ICMP, IGMP,SNMP, FTP, 802.1X, QoS, HTTPSSystem compatibilityONVIF, PSIA, CGI General functionalities User authentication, watermark, dual streamInterfaceInterfaceCommunication interface 1RJ45 10M / 100M Ethernet portOn-board storageBuilt-in Micro SD/SDHC/SDXC card slot, up to 64 GBGeneral-30 °C ~ 60 °C (-22 °F ~ 140 °F), humidity 95% or less (non-condensing)Power supplyDC12V ± 10%,	Network storage	NAS				
ProtocolsTCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, UPnP, ICMP, IGMP,SNMP, FTP, 802.1X, QoS, HTTPSSystem compatibilityONVIF, PSIA, CGI General functionalities User authentication, watermark, dual streamInterfaceInterfaceCommunication interface 1RJ45 10M / 100M Ethernet portOn-board storageBuilt-in Micro SD/SDHC/SDXC card slot, up to 64 GBGeneral-30 °C ~ 60 °C (-22 °F ~ 140 °F), humidity 95% or less (non-condensing)Power supplyDC12V ± 10%,	Alarm trigger	Motion detection, tampering alarm, network disconnect, IP address				
System compatibilityICMP, IGMP, SNMP, FTP, 802.1X, QoS, HTTPSSystem compatibilityONVIF, PSIA, CGI General functionalities User authentication, watermark, dual streamInterfaceRJ45 10M / 100M Ethernet portCommunication interface 1RJ45 10M / 100M Ethernet portOn-board storageBuilt-in Micro SD/SDHC/SDXC card slot, up to 64 GBGeneral-30 °C ~ 60 °C (-22 °F ~ 140 °F), humidity 95% or less (non-condensing)Power supplyDC12V ± 10%,		conflict, storage full, storage error				
System compatibilityONVIF, PSIA, CGI General functionalities User authentication, watermark, dual streamInterfaceInterfaceCommunication interface 1RJ45 10M / 100M Ethernet portOn-board storageBuilt-in Micro SD/SDHC/SDXC card slot, up to 64 GBGeneral-30 °C ~ 60 °C (-22 °F ~ 140 °F), humidity 95% or less (non-condensing)Power supplyDC12V ± 10%,	Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, UPnP,				
System compatibilityONVIF, PSIA, CGI General functionalities User authentication, watermark, dual streamInterfaceInterfaceCommunication interface 1RJ45 10M / 100M Ethernet portOn-board storageBuilt-in Micro SD/SDHC/SDXC card slot, up to 64 GBGeneral-30 °C ~ 60 °C (-22 °F ~ 140 °F), humidity 95% or less (non-condensing)Power supplyDC12V ± 10%,		ICMP, IGMP, SNMP, FTP, 802.1X, QoS, HTTPS				
dual streamInterfaceCommunication interface 1RJ45 10M / 100M Ethernet portOn-board storageBuilt-in Micro SD/SDHC/SDXC card slot, up to 64 GBGeneral-30 °C ~ 60 °C (-22 °F ~ 140 °F), humidity 95% or less (non-condensing)Power supplyDC12V ± 10%,	System compatibility					
InterfaceCommunication interface 1RJ45 10M / 100M Ethernet portOn-board storageBuilt-in Micro SD/SDHC/SDXC card slot, up to 64 GBGeneral-30 °C ~ 60 °C (-22 °F ~ 140 °F), humidity 95% or less (non-condensing)Power supplyDC12V ± 10%,	, , ,					
Communication interface 1RJ45 10M / 100M Ethernet portOn-board storageBuilt-in Micro SD/SDHC/SDXC card slot, up to 64 GBGeneral-30 °C ~ 60 °C (-22 °F ~ 140 °F), humidity 95% or less (non-condensing)Power supplyDC12V ± 10%,	Interface					
On-board storageBuilt-in Micro SD/SDHC/SDXC card slot, up to 64 GBGeneral-30 °C ~ 60 °C (-22 °F ~ 140 °F), humidity 95% or less (non-condensing)Power supplyDC12V ± 10%,		RI45 10M / 100M Ethernet port				
GeneralOperating conditions-30 °C ~ 60 °C (-22 °F ~ 140 °F), humidity 95% or less (non-condensing)Power supplyDC12V ± 10%,						
Operating conditions $-30 \ ^\circ C \ ^\circ 60 \ ^\circ C \ (-22 \ ^\circ F \ ^\circ 140 \ ^\circ F)$, humidity 95% or less (non-condensing)Power supplyDC12V $\pm 10\%$,	-					
Power supply DC12V ± 10%,		20% $\propto (0\%$ $(22\%$ $\times 140\%$) hyperidity 05% or loss (non-condensing)				
Power consumption Max 5.5W (7.5W with ICR on)						
	Power consumption	Max 5.5W (7.5W with ICR on)				